SAFETY DATA SHEET

26. HAIR COLOUR – FLAMMABLE – ETHANOL - UN1170

Date of Issue: 1st May 2022
Supersedes: N/A

1. Identification of Material and Supplier

Product Identifier: 26. HAIR COLOUR – FLAMMABLE- ETHANOL - UN1170

Other Means of Identification:
Perfumery products Class III Packaging Group II (Ethyl Alcohol >55%) and
Perfumery products Class III Packaging Group III (Ethyl Alcohol 24% to ≤55%).

Recommended Use/Product Type:
Cosmetic Skin Micropeel Products containing Salicylic Acid with Ethyl Alcohol.

AUSTRALIA

Supplier's Details: L'Oréal Australia Pty Ltd.
Address: 564 St Kilda Road,
Melbourne VIC 3004 Australia.
Telephone Number: (03) 8680 0000 (8am–6pm Mon to Fri).
Fax Number: (03) 8680 0009.
Emergency Telephone Number (Must be a 24 Hour Number):
(03) 8680 0800 (8am–6pm Mon to Fri).
(03) 8680 0866 (9am–5pm Mon to Fri).
0411 077 273 (After Hours).
Australian Poisons Information Centre:
13 11 26.
Email Address of the Person Responsible for this SDS:
sandor.berta@loreal.com.

NEW ZEALAND

Supplier's Details: L'Oréal New Zealand.
Address: Building 8, 9 Manu Street,
Othahuhu, Auckland 2024 New Zealand.
Telephone Number: +64 21 962 098 or +64 9583 4160 (8am–6pm Mon to Fri).
Fax Number: +64 9583 4188.
Emergency Telephone Number (Must be a 24 Hour Number):
+64 21 962 098 or +64 21245 1758 (8am–6pm Mon to Fri).
+64 21 962 098 (After Hours).
New Zealand Poisons Information Centre:
0800 764 766.
Email Address of the Person Responsible for this SDS:
Miu.TUALA@loreal.com Or Pieter.duplooy@loreal.com

C1 - Internal use

SAFETY DATA SHEET

26. HAIR COLOUR – FLAMMABLE – ETHANOL - UN1170

2. Hazard Identification

Hazard Classification: This product is classified as Hazardous according to the criteria of Safe Work Australia. Also classified as Dangerous Goods Class 3 Flammable Liquid according to the criteria of ADG Code 7.7 Edition.

NEW ZEALAND

Hazard Classification: This material is classified as a dangerous good according to criteria in New Zealand Standard 5433:2012 Transport of Dangerous Goods on Land.
This material is classified as hazardous according to criteria in the Hazardous Substances (Hazard Classification) Notice 2020.

NZ HSNO Classification*:* Category 3.1B Flammable (Ethanol >55%) or
Category 3.1C Flammable (Ethanol 24% to ≤55%)
Category 6.1D Acute Toxicity Oral- Category 4.
Category 8.3A Serious Eye Damage- Category 1.
Category 9.1D Hazardous to Aquatic Environment- Category 3.

BOTH COUNTRIES

GHS Classification of the substance or mixture:
Flammable Liquids - Category 3.
Serious Eye Damage/Eye Irritation- Category 2A.
Acute Aquatic Toxicity- Category 3.
Chronic Aquatic Toxicity- Category 3.

Allocation of Label Elements:
Pictograms:



GHS Signal word: **DANGER** (Ethyl Alcohol >55%) or
WARNING (Ethyl Alcohol 24% to ≤55%).

GHS Hazard statements: H225: Highly Flammable Liquid (Ethanol >55% or Isopropyl Alcohol) or
H226: Flammable liquid and vapour (Ethanol 24% to ≤55%).
H302: Harmful if swallowed.
H319: Causes serious eye irritation.
H402: Harmful to aquatic life.

C1 - Internal use

H412: Harmful to aquatic life with long lasting effects.

Precautionary statement(s):

General	P101: If medical advice is needed, have product container or label on hand.
	P102: Keep out of reach of children.
	P103: Read label before use.
	P104: Read Safety Data Sheet before use.
Prevention	P210: Keep away from heat/sparks/open flames/hot surfaces – No smoking.
	P233: Keep container tightly closed.
	P240: Ground/bond container and receiving equipment.
	P241: Use explosion-proof electrical/ ventilating/ lighting/equipment.
	P242: Use only non-sparking tools.
	P243: Take precautionary measures against static discharge.
	P264: Wash hands and face thoroughly after use.
	P270: Do not eat, drink or smoke when using this product.
	P273: Avoid release to the environment.
	P280: Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response	P301 + P312 IF SWALLOWED: call a POISON CENTER or Doctor if you feel unwell.
	P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
	P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P310: Immediately call a POISON CENTER or doctor/ physician.
	P330: Rinse mouth.
	P337 + P313: If eye irritation persists: Get medical advice.
	P370 + P378: In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
Storage	P403 + P235: Store in a well-ventilated place. Keep cool.
Disposal	P501: Dispose of contents/ container to an approved waste disposal plant in accordance with local/ regional/ national/ international regulations
Other Hazards	Not Specified.

3. Composition/Information on Ingredients

C1 - Internal use

SAFETY DATA SHEET

26. HAIR COLOUR – FLAMMABLE – ETHANOL - UN1170

Component/Substance	CAS Number	% by Weight	Hazardous Substance Classification
Ethanol	64-17-5	>55% ≤ 55%	H225, H319 H226, H319
Oleyl Alcohol	68002-94-8	0-30	
Lauryl Alcohol	112-53-8	0-30	H319
Other ingredients determined not to be hazardous		To 100	Not classified

4. First Aid Measures

General Advice: If poisoning occurs contact a doctor or Poisons Information Centre. Phone 13 11 26 from anywhere in Australia.

Eye: Rinse abundantly under flowing water for at least 15 minutes. If irritation develops seek medical attention. Splashes in the eye may cause immediate stinging and tears. Transient redness of the eye may also occur.

Skin: In case of skin contact, if irritation develops immediately wash off with plenty of water for at least 15 minutes. If irritation persists seek medical attention immediately.

Inhalation: If symptoms are experienced, remove source of contamination and move victim to fresh air immediately. If symptoms persist, seek medical attention. At relatively high vapour concentrations ethyl alcohol is an irritant to the nose and throat and may cause central nervous system depression.

Ingestion: Rinse mouth with water. If swallowed do not induce vomiting. Give one or two glasses of water or milk to drink. Seek medical attention immediately. May cause irritation of the gastrointestinal tract. Depression of the central nervous system may result in headache or dizziness.

Advice to Doctor: Treat symptomatically. If in eyes recheck after one week.

5. Fire Fighting Measures

Suitable Extinguishing Media:

Highly Flammable. In case of fire, all extinguishing media are suitable. For safety reasons do not use strong water jets.

Hazards from Combustion Products:

C1 - Internal use

May produce toxic fumes of carbon oxides.

Precautions for Fire Fighters and Special Protective Equipment:

If in the event of fire wear self-contained breathing apparatus. Use personal protective equipment. Keep containers cool with water spray. Closed containers may rupture when exposed to temperatures greater than 50°C. Vapour is heavier than air, distant ignition sources possible.

Hazchem Code: ●3YE (Packaging Group II or Ethyl Alcohol >55%) or
●3Y (Packaging Group III or Ethyl Alcohol 24% to ≤55%).

6. Accidental Release Measures

Emergency Procedures: UN 1170. Wear appropriate protective equipment. Spills will be slippery and highly flammable.

Methods and Materials for Containment and Clean Up Procedures:

Remove possible leaking containers. Remove all sources and ventilate area. Dilute small spills with water. For larger spills, wear protective equipment, dilute with water and absorb in inert material (sand or vermiculate). Shovel material into a suitable container and seal it. Wash the spill area with mild detergent to remove residue. Dispose of material in compliance with local, state and federal governments regulations. Do not allow the material to enter drains or waterways.

7. Handling and Storage

Precautions for Safe Handling:

This product is a Class 3 Flammable Liquid and should be transported and stored according to Dangerous Goods Regulations, Codes and Standards. Gloves (vinyl, rubber, plastic) may be worn when handling this material. Keep away from heat, flames or ignition source. Do not eat, drink or smoke in handling areas. Remove contaminated clothing and wash hands before eating.

Conditions for Safe Storage:

Store product upright in a cool place and out of direct sunlight. Store away from alkalis, corrosive and oxidising products. Use good personal hygiene practices. Store in accordance with Dangerous Goods Regulations and transport in accordance with ADG Code for Dangerous Goods Class 3.

8. Exposure Controls/Personal Protection

National Exposure Standards[1,2,3]:

C1 - Internal use

SAFETY DATA SHEET

26. HAIR COLOUR – FLAMMABLE – ETHANOL - UN1170

Chemical Name	*CAS No.*	*TWA (ppm)*	*TWA (mg/m^3)*	*STEL (ppm)*	*STEL (mg/m^3)*
Ethanol [1,2,3]	64-17-5	1000	1900	1000	-

TWA = Time-weighted average exposure standard.
STEL = Short term exposure limit standard.

1. Safe Work Australia. Exposure Standards for Atmospheric Contaminants (2019). See: https://www.safeworkaustralia.gov.au/doc/workplace-exposure-standards-airborne-contaminants-2019
2. Worksafe New Zealand. Workplace Exposure Standards and Biological Exposure Indices. (2020). See: https://www.worksafe.govt.nz/topic-and-industry/monitoring/exposure-standards-and-biological-exposure-indices/
3. US. NIOSH: Pocket Guide to Chemical Hazards Components See: https://www.cdc.gov/niosh/npg/default.html

Biological Limit Values: No Biological limit allocated.

Engineering Controls: Use in a well-ventilated area. Maintain air concentrations below exposure standards.
Flammable symbol or warning.



Personal Protective Equipment:
If ventilation is insufficient, a suitable respirator should be worn. When handling bulk quantities gloves (vinyl, plastic or rubber) shoud be worn when handling this product. It is recommended that protective clothing is worn e.g. aprons (vinyl, plastic or rubber) and safety shoes. Eye protection in the form of tightly fitting safety goggles and/or face shield should be worn.



9. Physical and Chemical Properties

Appearance:	Clear liquid.
Odour:	Characteristic fragrant alcohol odour.
pH:	Not determined.
Boiling Point (ºC):	78°C (Ethanol).
Vapour Pressure:	7.87 kPa @ 25°C.
Specific Gravity:	Not determined.
Flashpoint (ºC):	12°C (Ethanol).
Flammability Limits:	Highly flammable.

C1 - Internal use

Solubility in Water: Miscible.

10. Stability and Reactivity

Chemical Stability: Stable under normal conditions of handling, use and transportation.
Conditions to Avoid: Avoid heat and sources of ignition.
Incompatible Materials: Keep away from alkalis and corrosive substances.
Hazardous Decomposition Products: Decomposition not known to occur.
Hazardous Reactions: None known.

11. Toxicological Information

Inhalation: Prolonged inhalation may be harmful.
Skin contact: Causes skin irritation.
Eye contact: Causes serious eye damage
Ingestion: Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics: Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Skin irritation. May cause redness and pain.

Information on toxicological effects

Components	Species	Test Results
Acute Toxicity		
PRODUCT		
Acute Dermal:	ATEmix	149500 mg/kg
Acute Oral:	ATEmix	16430 mg/kg
ETHANOL (CAS 64-17-5)		
Acute Dermal:	Rabbit	LD50 > 20000 mg/kg
Inhalation-Vapor:	OECD 403 Rat	LC50 124.7 mg/l, 4h
Oral:	OECD 401 Rat	LD50 10470 mg/kg
LAURYL ALCOHOL (CAS 112-53-8)		
Acute Dermal:	OECD 402 Rabbit	LD50 8000 - 12000 mg/kg
Inhalation-Mist:	Rat	LC50 > 71 mg/l, 1 h Based on test data for

C1 - Internal use

		structurally similar materials.
Oral:	OECD 401 Rat	LD50 > 2000 mg/kg

OLEYL ALCOHOL (CAS 68002-94-8)

Acute Dermal:	Rabbit	LD50 8000 mg/kg Based on test data for structurally similar materials.
Oral:	OECD 401 Rat	LD50 > 2000 mg/kg

Skin corrosion/irritation:

PRODUCT Causes skin irritation. No adverse effects due to skin contact are expected.

ETHANOL (CAS 64-17-5)

Irritation corrosion- skin: OECD 404 Rabbit Not Irritating

LAURYL ALCOHOL (CAS 112-53-8)

Irritation corrosion- skin: OECD 404 Rabbit Not Irritating

OLEYL ALCOHOL (CAS 68002-94-8)

Irritation corrosion- skin: Rabbit Slightly Irritating

Serious eye damage/eye irritation:

PRODUCT Causes serious eye irritation.

ETHANOL (CAS 64-17-5)

Irritation Corrosion – Eye: OECD 405 Rabbit Irritating

LAURYL ALCOHOL (CAS 112-53-8)

Irritation Corrosion – Eye: OECD 405 Rabbit Irritating

OLEYL ALCOHOL (CAS 68002-94-8)

Irritation Corrosion – Eye: Rabbit Not Irritating

Respiratory or skin sensitization:

PRODUCT

Respiratory sensitization: Due to partial or complete lack of data the classification is not possible.

Skin sensitization:

PRODUCT Due to partial or complete lack of data the classification is not possible.

ETHANOL (CAS 64-17-5)

Skin sensitization: OECD 406 Guinea pig Not Sensitizing

LAURYL ALCOHOL (CAS 112-53-8)

Skin sensitization: OECD 406 Guinea pig Not Sensitizing

OLEYL ALCOHOL (CAS 68002-94-8)

Skin sensitization: Rabbit Not Sensitizing

Mutagenicity

C1 - Internal use

26. HAIR COLOUR – FLAMMABLE – ETHANOL - UN1170

PRODUCT

Germ cell mutagenicity: Due to partial or complete lack of data the classification is not possible.

ETHANOL (CAS 64-17-5)

Mutagenicity: In vitro and in vivo tests did not show mutagenic effects.

LAURYL ALCOHOL (CAS 112-53-8)

Mutagenicity: In vitro and in vivo tests did not show mutagenic effects.

OLEYL ALCOHOL (CAS 68002-94-8)

Mutagenicity: In vitro and in vivo tests did not show mutagenic effects.

Carcinogenicity

PRODUCT

Carcinogenicity: Not classifiable as to carcinogenicity to humans. Due to partial or complete lack of data the classification is not possible.

IARC Monographs: Overall Evaluation of Carcinogenicity
Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052):
Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens:
Not listed.

Reproductive toxicity

PRODUCT Possible reproductive hazard.

ETHANOL (CAS 64-17-5)

Developmental effects:	OECD 414 Rat	> 20000 ppm

LAURYL ALCOHOL (CAS 112-53-8)

Developmental effects:	OECD 422 Rat	2000 mg/kg bw/d

OLEYL ALCOHOL (CAS 68002-94-8)

Developmental effects:	OECD 422 Rat	NOAEL 2000 mg/kg bw/d

ETHANOL (CAS 64-17-5)

Reproductivity:	OECD 416 Rat	20700 mg/kg bw/d No effects on fertility

LAURYL ALCOHOL (CAS 112-53-8)

Reproductivity:	OECD 422 Rat	NOAEL 2000 mg/kg bw/d

OLEYL ALCOHOL (CAS 68002-94-8)

Reproductivity:	OECD 422 Rat	NOAEL 2000 mg/kg bw/d

Specific target organ toxicity - single exposure

PRODUCT Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity - repeated exposure

C1 - Internal use

26. HAIR COLOUR – FLAMMABLE – ETHANOL - UN1170

PRODUCT Due to partial or complete lack of data the classification is not possible.

ETHANOL (CAS 64-17-5)

Repeated Dose 90 Day Oral Toxicity:

OECD 408 Rat NOAEL 1730 mg/kg bw/d

LAURYL ALCOHOL (CAS 112-53-8)

Specific target organ toxicity - repeated exposure:

Rat NOAEL 1127 mg/kg bw/d 90d

Aspiration hazard:

PRODUCT Due to partial or complete lack of data the classification is not possible.

Further information: The reference to any animal testing for individual constituents mentioned in this document is based on public, third-party data.

12. Ecological Information

Ecotoxicity:

PRODUCT The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
ETHANOL (CAS 64-17-5)		
Aquatic Toxicity:		
Acute		
Algae:	Pseudokirchneriella subcapitata	EC50 22200 mg/l, 96 h
Crustacea:	Ceriodaphnia dubia	EC50 5012 mg/l, 48 h
Fish:	Pimephales promelas	LC50 15300 mg/l, 96 h
Other:	Activated sludge of a predominantly domestic sewage	IC50 > 1000 mg/l, 3 h
Chronic		
Crustacea:	Daphnia magna	NOEC 9.6 mg/l, 9 d
Fish:	OECD 212 Danio rerio	NOEC 250 mg/l, 120 h
LAURYL ALCOHOL (CAS 112-53-8)		
Acute		
Algae:	Desmodesmus subspicatus	EC50 0.66 mg/l, 72 h
Crustacea:	Daphnia magna	EC50 0.765 mg/l, 48 h

C1 - Internal use

Fish:	Pimephales promelas	LC50 1.01 mg/l, 96 h
Other:	Tetrahymena pyriformis	EC50 1.58 mg/l, 48 h
Chronic		
Algae:	Desmodesmus subspicatus	NOEC 0.085 mg/l, 72 h
Crustacea:	Daphnia magna	NOEC 0.014 mg/l, 21 d

OLEYL ALCOHOL (CAS 68002-94-8)

Acute		
Algae:	OECD 201 Algae	EC50 250 mg/l
Fish:	OECD 203 Fish	LC50 > 1000 mg/l

Persistence and degradability:

Biodegradability:

Percent degradation (Aerobic biodegradation)

ETHANOL		84 % Readily Biodegradable Test Duration: 20 d
LAURYL ALCOHOL		
	OECD 301 D	79 % Readily Biodegradable Test Duration: 28 d
OLEYL ALCOHOL		
	OECD 301 D	87 % Not Readily Biodegradable Test Duration: 28 d

Bioaccumulative potential:

Partition coefficient n-octanol / water (log Kow)

ETHANOL		-0.31
LAURYL ALCOHOL		
	OECD 117	5.4

Mobility in soil: No data available.

Other adverse effects: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal Considerations

Disposal Methods: Recover if possible and dispose of in accordance with local, state and federal government regulations.

Special Requirements for Landfill or Incineration:

Empty containers should be disposed of to landfill in domestic garbage collection. The local waste authority should be consulted prior to disposal of bulk quantities.

C1 - Internal use

SAFETY DATA SHEET

26. HAIR COLOUR – FLAMMABLE – ETHANOL - UN1170

14. Transport Information

AUSTRALIA- ADG

UN Number:	1170.
UN Proper Shipping Name:	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION).
Class & Subsidiary Risk:	Class 3 (Australia). 3.1B (New Zealand).
Packaging Group:	II.
Special Precautions:	SP144, P001, IBC02, T4 and TP1.
Hazchem Code:	●3YE.

or

UN Number:	1170.
UN Proper Shipping Name:	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION).
Class & Subsidiary Risk:	Class 3 (Australia. 3.1C (New Zealand).
Packaging Group:	III.
Special Precautions:	SP144, SP223, P001, IBC03, LP01, T2 and TP1.
Hazchem Code:	●3Y.

NEW ZEALAND

Relevant Information: Hazard Class 3.
Identification number of the hazard 33.



IMDG

UN/ID No.:	UN1170.
Proper shipping name:	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION).
Hazard class:	3.
Packing group:	II.
Special Precautions:	SP144, E2, P001, IBC02, T4 and TP1.

Or

UN/ID No.:	UN1170.
Proper shipping name:	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION).
Hazard class:	3.
Packing group:	III.
Special Precautions:	SP144, SP223, SP904, SP955, E1, P001, LP01 and IBC03.

ICAO/IATA

UN/ID No.:	ID8000.
Proper shipping name:	CONSUMER COMMODITY.
Hazard class:	9.
Packing group:	Dangerous Goods Packing Instruction Y963.

15. Regulatory Information

C1 - Internal use

SAFETY DATA SHEET

26. HAIR COLOUR – FLAMMABLE – ETHANOL - UN1170

AUSTRALIA

SUSMP: Not Scheduled.

Competition and Consumer Act:
Cosmetic ingredients must be labelled.

Industrial Chemicals Act: Ingredients are in the Australian Inventory of Industrial Chemicals (AIIC) and/or in compliance with the *Industrial Chemicals Act* 2019 and the Industrial *Chemicals (General) Rules 2019.*

NEW ZEALAND

Dangerous Goods Regulations:
Symbols are required for bulk storage and containers only and not on small packaged goods for consumers.



Risk phases are required for bulk storage and containers only.

Risk-phrase(s)

F: Flammable.
Xn: Harmful.
Xi: Irritant.
R11: Highly Flammable.
R22: Harmful if swallowed.
R41: Risk of serious damage to eyes.
R67: Vapours may cause drowsiness and dizziness.
R52: Harmful to aquatic organisms.
R53: May cause long term adverse effects in the aquatic environment.

Or combination risk phases as appropriate.

S-phrase(s)

S2: Keep out of the reach of children.
S7: Keep container tightly closed.
S13: Keep away from food, drink and animal feeding stuffs.
S16: Keep away from sources of ignition – no smoking.
S23: Do not breathe gas/fumes/vapour/spray.
S24: Avoid contact with skin.
S25: Avoid contact with eyes.
S26: In case of contact with eyes, rinse immediately with plenty of water and contact a doctor or Poisons Information Centre.
S46: If swallowed, seek medical advice immediately and show container or label.

Health & Safety at Work (Hazardous Substances) Regulations 2017:

C1 - Internal use

SAFETY DATA SHEET

26. HAIR COLOUR – FLAMMABLE – ETHANOL - UN1170

HSNO Regulations: The HSNO Approval Number for this Group Standard is HSR002552 (Cosmetic Products Group Standard). Substances must comply with the Standard.

Identification and labelling Regulations:
Hazardous Substances (Hazard Classification) Notice 2020.
Consolidated Hazardous Substances (Labelling) Notice 2017.

Storage and handling: Consolidated Hazardous Substances (Hazardous Property Controls) Notice 2017.

Packaging Regulations: Consolidated Hazardous Substances (Packaging) Notice 2017.
Disposal Regulations: Consolidated Hazardous Substances (Disposal) Notice 2017.

Other Regulations or Notices:
Hazardous Substances (Forms and Information) Notice 2017
Consolidated Hazardous Substances (Safety Data Sheets) Notice 2017.
Consolidated Hazardous Substances (Importers and Manufacturers) Notice 2015.
Hazardous Substances (Amendments and Revocations) Notice 2020.
Hazardous Substances (Enforcement Officer Qualifications) Notice 2015.

Tracking: Not required under Consolidated Hazardous Substances (Hazardous Property Controls) Notice 2017.

Certified Handlers: Required under Health and Safety at Work (Hazardous Substances) Regulations 2017.

16. Other Information

Date of Issue: 1st May 2022
Supersedes: N/A
Version Number: *1*
Disclaimer: The information contained in this SDS was compiled using the latest and most reliable information available. The information is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Similarly, no warranty, expressed or implied, shall be created by or inferred from any statement or omission from this SDS nor will L'Oréal assume any liability for any loss or damage arising out of the use of this information. It is solely the responsibility of the user to determine safe conditions for use of this product.

C1 - Internal use

26. HAIR COLOUR – FLAMMABLE – ETHANOL - UN1170

END OF SDS

C1 - Internal use