# AMERICAN INTERNATIONAL INDUSTRIES

## Safety Data Sheet
## Seche Matte Top Coat

Australia

## SECTION 1: Identification of the material and supplier

### Product identifier

| | |
|---|---|
| **Product name** | Seche Matte Top Coat |
| **Product number** | 37844 (30-11445 Blend) |

### Recommended use of the chemical and restrictions on use

| | |
|---|---|
| Recommended use | Personal care product (nail cosmetic) for salon and consumer use |
| Restrictions on use | Use only as directed on the label. |

### Details of the supplier in Australia (importer)

| | |
|---|---|
| Company | Professional Salon Brands Pty Ltd |
| Address | 5 Distribution Avenue, Molendinar QLD 4214, Australia |
| Telephone | (07) 5564 6720 |
| Fax | (07) 5564 6005 |

### Emergency telephone number: Australia

| | |
|---|---|
| Poisons Information Centre | 13 11 26 (24 hours) |
| Fire, police, ambulance | 000 |
| Company contact | John Restaino, Managing Director<br>(BH) (07) 5564 6720<br>(AH) 0416 158 057 |

### Manufacturer

| | |
|---|---|
| Name | American International Industries |
| Address | 2220 Gaspar Ave, Los Angeles, CA 90040, USA |
| Telephone | +1 323 728 2999 |
| Emergency (USA) | Chem-Tel +1 800 255 3924 |

## SECTION 2: Hazard identification

### Classification of the hazardous chemical

Classified as **hazardous** according to the criteria of the Globally Harmonized System of Classification and Labelling of Chemicals, Revision 7 (GHS 7), as adopted by the Work Health and Safety Regulations (Australia).

– Flammable liquids, Category 2, H225
– Serious eye damage / eye irritation, Category 2A, H319
– Specific target organ toxicity (single exposure): narcotic effects, Category 3, H336

Classified as **Dangerous Goods** for transport by road and rail according to the Australian Code for the Transport of Dangerous Goods by Road & Rail (ADG Code), Class 3.

### Label elements

### Hazard pictograms



GHS02 Flame



GHS07 Exclamation mark

**Signal word** **DANGER**

**Hazard statement(s)**

| | |
|---|---|
| H225 | Highly flammable liquid and vapour. |
| H319 | Causes serious eye irritation. |
| H336 | May cause drowsiness or dizziness. |

**Precautionary statement(s): Prevention**

| | |
|---|---|
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P233 | Keep container tightly closed. |
| P240 | Ground and bond container and receiving equipment. |
| P241 | Use explosion proof electrical, ventilating and lighting equipment. |
| P242 | Use non sparking tools. |
| P243 | Take action to prevent static discharges. |
| P261 | Avoid breathing vapours. |
| P264 | Wash hands thoroughly after handling. |
| P271 | Use only outdoors or in a well ventilated area. |
| P280 | Wear protective gloves and eye protection. |

**Precautionary statement(s): Response**

| | |
|---|---|
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. |
| P304+P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P312 | Call a POISON CENTRE or doctor if you feel unwell. |
| P337+P313 | If eye irritation persists: Get medical advice or attention. |
| P370+P378 | In case of fire: Use dry chemical powder, carbon dioxide or alcohol resistant foam to extinguish. |

**Precautionary statement(s): Storage**

| | |
|---|---|
| P403+P233 | Store in a well ventilated place. Keep container tightly closed. |
| P403+P235 | Store in a well ventilated place. Keep cool. |
| P405 | Store locked up. |

**Precautionary statement(s): Disposal**

| | |
|---|---|
| P501 | Dispose of contents and container in accordance with local, state and federal regulations. |

**Other hazards**

Vapours are heavier than air and may travel to a source of ignition and flash back.

## SECTION 3: Composition and information on ingredients

**Mixture**

| Chemical name | CAS number | Proportion (% w/w) |
|---|---|---|
| n-Butyl acetate | 123-86-4 | 30 to 40 |
| Ethyl acetate | 141-78-6 | 25 to 35 |
| Nitrocellulose | 9004-70-0 | 10 to 20 |
| Isopropyl alcohol (propan-2-ol) | 67-63-0 | 5 to 10 |
| Other ingredients determined not to be hazardous | Not applicable | To 100 |

## SECTION 4: First aid measures

**Description of first aid measures**

For advice, contact the Poisons Information Centre on 13 11 26 (Australia) or a doctor. In an emergency call 000.

| | |
|---|---|
| Inhalation | Remove to fresh air and keep at rest in a position comfortable for breathing. Keep warm. If breathing is irregular or stops, give artificial respiration and call 000. Seek medical advice if unwell. |
| Skin contact | Remove contaminated clothing. Wash skin with plenty of soap and water. Seek medical advice if irritation develops. |
| Eye contact | Rinse thoroughly with plenty of water for at least 15 minutes, holding eyelids open. Remove contact lenses if present and easy to do. Seek medical attention if irritation persists. |
| Ingestion | Rinse mouth with water. Do NOT induce vomiting. Contact the Poisons Information Centre or a doctor immediately. Never give anything by mouth to an unconscious person. |
| Protection of first aiders | Wear suitable protective equipment. Remove ignition sources. |

**Most important symptoms and effects, both acute and delayed**

| | |
|---|---|
| Inhalation | Drowsiness, dizziness, headache, nausea. |
| Skin | Redness, dryness, cracking. |
| Eyes | Redness, pain, watering, blurred vision. |
| Ingestion | Nausea, vomiting, drowsiness. |

**Indication of any immediate medical attention and special treatment needed**

Treat symptomatically. Show this SDS to the doctor.

## SECTION 5: Fire fighting measures

| | |
|---|---|
| Suitable extinguishing media | Alcohol resistant foam, dry chemical powder, carbon dioxide. |
| Unsuitable extinguishing media | Do not use a direct water jet; it may spread the fire. Water spray may be used to cool fire exposed containers. |
| Specific hazards | Highly flammable. Vapours are heavier than air, may spread along the ground and form explosive mixtures with air. Containers may rupture when heated. Empty containers retain flammable residue. Combustion produces dense black smoke and may release carbon oxides and nitrogen oxides. |
| Advice for fire fighters | Wear self contained breathing apparatus (SCBA) and full protective clothing. Cool containers with water spray. |
| Hazchem code | **•3YE** |

## SECTION 6: Accidental release measures

| | |
|---|---|
| Personal precautions, protective equipment and emergency procedures | Remove all ignition sources. Ventilate the area. Avoid contact with skin and eyes and avoid breathing vapours. Wear protective equipment as described in Section 8. |
| Environmental precautions | Prevent spillage from entering drains, sewers or waterways. If a large quantity enters drains or waterways, notify the local council or the state environment protection authority. |
| Methods and materials for containment and cleaning up | Small spills (salon or retail quantities): absorb with inert material such as sand, vermiculite or absorbent pads and place in a closed container for disposal. Large spills: contain with sand or earth using non sparking tools, collect for disposal, and call 000 if there is a risk of fire. Do not flush to drain. |

## SECTION 7: Handling and storage

| | |
|---|---|
| Precautions for safe handling | Use in a well ventilated area. Keep away from heat, sparks and open flames. Avoid contact with eyes and prolonged or repeated skin contact. Do not eat, drink or smoke while handling. Wash hands after use. |
| Conditions for safe storage, including any incompatibilities | Store in a cool, dry, well ventilated place away from direct sunlight, heat and ignition sources. Keep containers tightly closed and upright. Store away from incompatible materials (Section 10). Store in accordance with the WHS Regulations and AS 1940 The storage and handling of flammable and combustible liquids. |

## SECTION 8: Exposure controls and personal protection

### Control parameters

Workplace exposure limits: Safe Work Australia, Workplace Exposure Limits for Airborne Contaminants (effective 1 December 2026).

| Ingredient | TWA (8 hours) | STEL (15 minutes) |
|---|---|---|
| n-Butyl acetate | 50 ppm | 100 ppm |
| Ethyl acetate | 200 ppm (720 mg/m$^3$) | 400 ppm (1440 mg/m$^3$) |
| Nitrocellulose | Not established | Not established |
| Isopropyl alcohol (propan-2-ol) | 200 ppm | 400 ppm |

TWA: time weighted average. STEL: short term exposure limit.

Biological limit values: None established for the ingredients.

### Exposure controls

Appropriate engineering controls: Salon, retail, warehouse and household settings: ensure adequate general ventilation. Where vapours may accumulate (for example, bulk decanting), use local exhaust ventilation and explosion proof equipment.

### Personal protective equipment

| | |
|---|---|
| Eye and face protection | Not normally required for salon or consumer use. For bulk handling, wear safety glasses or goggles complying with AS/NZS 1337. |
| Hand protection | Not normally required for salon or consumer use. For repeated or prolonged contact, wear chemical resistant gloves complying with AS/NZS 2161. |
| Body protection | Wear protective clothing to prevent skin contact when handling bulk quantities. |
| Respiratory protection | Not normally required with adequate ventilation. If exposure limits may be exceeded, use an approved respirator with an organic vapour (Type A) filter, selected and used in accordance with AS/NZS 1715 and AS/NZS 1716. |

## SECTION 9: Physical and chemical properties

| | |
|---|---|
| Appearance | Viscous liquid |
| Odour | Solvent |
| Odour threshold | No data available |
| pH | No data available |
| Melting point / freezing point | No data available |
| Initial boiling point and boiling range | >77°C |
| Flash point | 1.5°C |
| Evaporation rate | No data available |

| | |
|---|---|
| Flammability | Highly flammable liquid. Vapours may form explosive mixtures with air. |
| Upper / lower flammability limits | No data available |
| VOC | No data available |
| Vapour pressure | No data available |
| Vapour density | No data available |
| Relative density | 0.95 to 1.05 at 20°C |
| Solubility | No data available |
| Partition coefficient: n-octanol/water | No data available |
| Auto ignition temperature | No data available |
| Decomposition temperature | No data available |
| Viscosity | Variable |
| Explosive properties | No data available |
| Oxidising properties | No data available |

## SECTION 10: Stability and reactivity

| | |
|---|---|
| Reactivity | No specific reactivity hazards known under normal conditions of use. |
| Chemical stability | Stable under recommended storage and handling conditions. |
| Possibility of hazardous reactions | Vapours may form explosive mixtures with air. |
| Conditions to avoid | Heat, sparks, open flames, static discharge, direct sunlight. |
| Incompatible materials | Strong oxidising agents, strong acids and alkalis, alkali metals, fluorine, hydrides. |
| Hazardous decomposition products | Thermal decomposition may release carbon oxides and nitrogen oxides. |

## SECTION 11: Toxicological information

| | |
|---|---|
| Likely routes of exposure | Inhalation, skin contact, eye contact. Ingestion is unlikely in normal use. |
| Acute toxicity | Not classified. Oral LD50 >2000 mg/kg; dermal LD50 >2000 mg/kg; inhalation LC50 >20 mg/L (manufacturer data). Vapours may cause drowsiness and dizziness. |
| Skin corrosion / irritation | Not classified. Repeated or prolonged contact may cause dryness, cracking or dermatitis. |
| Serious eye damage / irritation | Causes serious eye irritation. |
| Respiratory or skin sensitisation | Not classified. No data available. |
| Germ cell mutagenicity | Not classified. No data available. |
| Carcinogenicity | Not classified. No ingredient is classified as a carcinogen. |
| Reproductive toxicity | Not classified. No data available. |
| STOT (single exposure) | May cause drowsiness or dizziness. |
| STOT (repeated exposure) | Not classified. No data available. |
| Aspiration hazard | Not classified. No data available. |

## SECTION 12: Ecological information

| | |
|---|---|
| Ecotoxicity | Aquatic toxicity: LC50 >60 mg/L (fish); EC50 >170 mg/L (daphnia). Do not allow product to enter drains or waterways. |
| Persistence and degradability | No data available. |
| Bioaccumulative potential | No data available. |
| Mobility in soil | No data available. |
| Other adverse effects | No data available. |

## SECTION 13: Disposal considerations

| | |
|---|---|
| Disposal methods | Do not pour to drain or dispose of bulk quantities with general waste. Dispose of product and contaminated absorbent through a licensed waste contractor or a council household chemical collection point, in accordance with local, state and territory regulations. |
| Containers | Empty containers may retain flammable residue. Do not cut, puncture or weld. Dispose of in accordance with local regulations. |

## SECTION 14: Transport information

| | Road and rail (ADG Code) | Sea (IMDG Code) | Air (IATA) |
|---|---|---|---|
| UN number | 1263 | 1263 | 1263 |
| Proper shipping name | PAINT | PAINT | PAINT |
| Transport hazard class | 3 | 3 | 3 |
| Subsidiary risk | None | None | None |
| Packing group | II | II | II |
| Hazchem code | •3YE | Not applicable | Not applicable |
| EmS | Not applicable | F-E, S-E | Not applicable |
| Environmental hazard | No | Not a marine pollutant | No |

| | |
|---|---|
| Limited quantities | ADG Code: may be transported as limited quantities in inner packagings not exceeding 5 L, subject to ADG Chapter 3.4. |
| Air transport (retail packs) | Retail packs may be shipped as ID8000, Consumer commodity, Class 9, Packing Instruction Y963, where all IATA conditions are met. |
| Special precautions | Keep away from ignition sources. Segregate from incompatible dangerous goods in accordance with the ADG Code. |

## SECTION 15: Regulatory information

**Safety, health and environmental regulations specific to the product**

| | |
|---|---|
| Work Health and Safety Regulations | Hazardous chemical (GHS 7). |
| ADG Code | Dangerous Goods, Class 3, Packing Group II. |
| Poisons Standard (SUSMP) | Not scheduled. |
| Australian inventory | All ingredients are listed on the Australian Inventory of Industrial Chemicals (AIIC). |
| Other | AS 1940 The storage and handling of flammable and combustible liquids. Safe Work Australia Model Code of Practice: Managing risks of hazardous chemicals in the workplace. |

## SECTION 16: Other information

**Full text of hazard statements referenced in Section 2**

| | |
|---|---|
| H225 | Highly flammable liquid and vapour. |
| H319 | Causes serious eye irritation. |
| H336 | May cause drowsiness or dizziness. |

### Revision information

| | |
|---|---|
| Date of preparation | 2026-11-16 |
| Version | Version AU 1.0. Australian format prepared from the American International Industries SDS (Version 1.1, revision date 2026-11-11), with Australian classification, transport and regulatory information. |
| Review date | Within five years of the date of preparation, or earlier if new hazard information becomes available. |

### Abbreviations

ADG: Australian Dangerous Goods Code. AIIC: Australian Inventory of Industrial Chemicals. CAS: Chemical Abstracts Service. GHS: Globally Harmonized System. IATA: International Air Transport Association. IMDG: International Maritime Dangerous Goods Code. SCBA: self contained breathing apparatus. STEL: short term exposure limit. STOT: specific target organ toxicity. SUSMP: Standard for the Uniform Scheduling of Medicines and Poisons. TWA: time weighted average.

### References

Safe Work Australia: Model Code of Practice: Preparation of safety data sheets for hazardous chemicals; Model Code of Practice: Labelling of workplace hazardous chemicals; Workplace Exposure Limits for Airborne Contaminants. Australian Code for the Transport of Dangerous Goods by Road & Rail. Poisons Standard (SUSMP).

### Further information / disclaimer

The information in this SDS is based on data supplied by the manufacturer and is believed to be accurate at the date of preparation; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information relates only to the specific product and may not be valid if the product is combined with other materials. Users should make their own assessment of workplace risk in accordance with the WHS Regulations.